

Rugged Handheld POS Solution



Rugged Handheld POS Solution

The ST400 series POS Handhelds feature 4.3" touch screens in compact and robust packages for point-of-service/sale applications, inventory management, and field applications.

With the high performance processors, and large memory and flash, these POS handhelds enhance performance, energy efficiency, and storage capacity.

Emphasizing superior integration and handling, the ST400 series handhelds offer options for embedded POS-centric peripherals, including magnetic stripe and RFID readers, cameras, and powerful barcode scanners.

Designed for real-life handling in harsh operating conditions, the rugged ST400 series handhelds feature drop-protection, IP-rated for dust and water-proof operations, and hot-swappable batteries for extended performance.

SUMO Technologies POS Handhelds provide the precise features needed to streamline operations and improve productivity, accurate data collection and service efficiency, and secure payment transactions.

Features




- ▶ Resistive or Capacitive Touch Screen
- ▶ Slim and lightweight design
- ▶ IP54 dust and water-splash proof enclosure with IP65 front panel
- ▶ Dynamic virtual keyboard
- ▶ Support for Windows® CE and Windows® Mobile
- ▶ WLAN and Bluetooth

Major Options^[1]

- ▶ Magnetic stripe reader (MSR)
- ▶ 2D barcode scanner, also reads 1D
- ▶ RFID reader
- ▶ 3 megapixel back camera with LED flash

[1] = See specification for supported models

Rugged Handheld POS Solution

Specification			
System	ST430SC	ST432SC	ST433SC
CPU	ARM 800MHz		
RAM	512MB		
Storage	4GB Flash		
Operating System	Windows CE 6.0 or Windows Mobile 6.X	Windows CE 6.0 or Windows Mobile 6.5	
Display	4.3" TFT-LCD with resistive touch; outdoor-viewable display	4.3" TFT-LCD with capacitive touch	
Display Resolution	272 x 480	480 x 800	
Control Switch and Buttons	1 power button, 4 front buttons, 2 trigger buttons	1 power button, 2 trigger buttons	
Indicator	1 power-on LED indicator, 1 WLAN enable/communication indicator, 1 MSR indicator	N/A	
Speaker and Microphone	1 built-in speaker, 1 mono microphone		N/A
Network Interface			
WLAN	Built-in IEEE 802.11a/b/g/n WLAN		
Bluetooth	Bluetooth 2.1		
I/O Ports			
USB Port	1 (USB 1.1)	1 (mini USB for charging and ActiveSync only)	
Audio Jack	1 (2.5mm stereo headset and microphone jack)	1 (2.5mm stereo headset and microphone jack)	N/A
DC-in	1, 1.3mm	1 via mini USB	
Cradle Charging Interface	1	2 external power pins	
Micro SD Slot	N/A	Yes, up to 32GB	
Mechanical and Environmental			
AC/DC Adapter	Input: 100 – 240V AC; Output: 5V DC, 3A	Input: 100 – 240V AC; Output: 5V DC, 2A	
Battery Pack	Replaceable rechargeable Li-ion battery 3760mAh, 3.7V	Replaceable, rechargeable Li-ion battery 2500mAh, 3.7V	
Backup Battery	180 mAh	N/A	
Enclosure	PC+ABS, TPR		
Stylus	Yes, non-electronic tip	N/A	
Dimensions (H x W x D)	6.3 x 3.4 x 1.2 in/ 160 x 86 x 30 mm	5.5 x 3 x 0.85 in/ 139 x 76 x 21.5 mm	5.9 x 3 x 0.55 in/ 150 x 76 x 14 mm
Weight	0.9 lbs/ 415 g	0.39 lbs/ 178 g	0.41 lbs/ 186 g
Water and Dust Resistance	System: IP54; Front Panel: IP65	Front Panel: IP54	Front Panel: IP54
Drop, Vibration and Shock Resistance	N/A	MIL-STD-810G	MIL-STD-810G
Regulatory	FCC Class B, CE, C-Tick, UL, CB, RoHS compliant	FCC Class B, CE, C-Tick, RoHS compliant	
Temperature	Operation: 0°C – 40°C; Storage: -20°C – 60°C		
Humidity	0% – 90% non-condensing		
Data Capture Modules (optional)			
MSR	Triple track readers (ISO TK1, 2 & 3), JIS & AAMVA compliant	N/A	Triple track readers (ISO TK1, 2 & 3), JIS & AAMVA compliant
Barcode Scanner	1D or 2D scanner	2D scanner, reads 1D also	N/A
RFID Reader	HF 13.56MHz, ISO standard 15693, 14443A(B), 18000-3 mode-1	N/A	N/A
Camera	N/A	3 megapixel back camera with LED flash, auto focus	N/A



For more information, including pricing, availability and detailed features please look at our web site at www.sumotech.com or email sales@sumotech.com

SUMO Technologies Ltd, Manor Chambers, Marygate, YORK YO30 7BH
Tel: +44 (0) 1904 670670 Fax: +44 (0) 1904 670570

All specifications are subject to change without notice.

SUMO, Masters of Technology, ST430SC, ST432SC and ST433SC are trademarks of SUMO Technologies Ltd. All other products and services are trademarks or service marks of their respective companies, and are acknowledged. E&OE